查询REG1117供应商

SBVS001D − OCTOBER 1992 − REVISED JULY 2004

800mA and 1A Low Dropout Positive Regulator 1.8V, 2.5V, 2.85, 3.3V, 5V, and Adjustable

FEATURES

- FIXED AND ADJUSTABLE VERSIONS
- 2.85V MODEL FOR SCSI-2 ACTIVE TERMINATION
- OUTPUT CURRENT:
  REG1117: 800mA max
  REG1117A: 1A max
- OUTPUT TOLERANCE: ±1% max
- DROPOUT VOLTAGE:
  REG1117: 1.2V max at I_O = 800mA
  REG1117A: 1.3V max at I_O = 1A
- INTERNAL CURRENT LIMIT
- THERMAL OVERLOAD PROTECTION
- SOT-223 AND DDPAK SURFACE-MOUNT PACKAGES

APPLICATIONS

- SCSI-2 ACTIVE TERMINATION
- HAND-HELD DATA COLLECTION DEVICES
- HIGH EFFICIENCY LINEAR REGULATORS
- BATTERY-POWERED INSTRUMENTATION
- BATTERY MANAGEMENT CIRCUITS FOR NOTEBOOK AND PALMTOP PCs
- CORE VOLTAGE SUPPLY: FPGA, PLD, DSP, CPU

DESCRIPTION

The REG1117 is a family of easy-to-use three-terminal voltage regulators. The family includes a variety of fixed- and adjustable-voltage versions, two currents (800mA and 1A) and two package types (SOT-223 and DDPAK). See the chart below for available options.

Output voltage of the adjustable versions is set with two external resistors. The REG1117 low dropout voltage allows its use with as little as 1V input-output voltage differential.

Laser trimming assures excellent output voltage accuracy without adjustment. An NPN output stage allows output stage drive to contribute to the load current for maximum efficiency.

	800mA		1A	
VOLTAGE	SOT-223	DDPAK	SOT-223	DDPAK
1.8V			✓	✓
2.5V			✓	✓
2.85V	✓			
3.3V	✓	✓		
5V	✓			✓
Adjustable	✓		✓	✓

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

All trademarks are the property of their respective owners.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 1992−2004, Texas Instruments Incorporated

ABSOLUTE MAXIMUM RATINGS(1)

Power Dissipation	Internally Limited
Input Voltage	+15V
Operating Junction Temperature Range	−40°C to +125°C
Storage Temperature Range	−65°C to +150°C
Lead Temperature (soldering, 10s)(2)	+300°C

(1) Stresses above these ratings may cause permanent damage.
(2) See *Soldering Methods* section.

This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

CONNECTION DIAGRAM

Front View



NOTE: (1) Adjustable−Voltage Model.

PACKAGE/ORDERING INFORMATION(1)

PRODUCT	V_O/I_O	PACKAGE-LEAD	PACKAGE DESIGNATOR	OPERATING TEMPERATURE RANGE	PACKAGE MARKING	ORDERING NUMBER	TRANSPORT MEDIA, QUANTITY
REG1117-2.85	2.85/800mA	SOT223-3	DCY	−40°C to +125°C	BB11172	REG1117-2.85	Rails, 80
						REG1117-2.85	Tape and Reel, 2500
REG1117-3.3	3.3/800mA	SOT223-3	DCY	−40°C to +125°C	BB11174	REG1117-3.3	Rails, 80
						REG1117-3.3	Tape and Reel, 2500
REG1117F-3.3	3.3/800mA	DDPAK-3	KTT	−40°C to +125°C	BB1117F4	REG1117F-3.3KTTT	Tape and Reel, 50
						REG1117F-3.3/500	Tape and Reel, 500
REG1117-5	5V/800mA	SOT223-3	DCY	−40°C to +125°C	BB11175	REG1117-5	Rails, 80
						REG1117-5	Tape and Reel, 2500
REG1117	Adj./800mA	SOT223-3	DCY	−40°C to +125°C	BB1117	REG1117	Rails, 80
						REG1117	Tape and Reel, 2500
REG1117A-1.8	1.8V/1A	SOT223-3	DCY	−40°C to +125°C	R111718	REG1117A-1.8	Rails, 80
						REG1117A-1.8	Tape and Reel, 2500
REG1117FA-1.8	1.8/1A	DDPAK-3	KTT	−40°C to +125°C	REG1117FA1.8	REG1117FA-1.8KTTT	Tape and Reel, 50
						REG1117FA-1.8/500	Tape and Reel, 500
REG1117A-2.5	2.5/1A	SOT223-3	DCY	−40°C to +125°C	R111725	REG1117A-2.5	Rails, 80
						REG1117A-2.5	Tape and Reel, 2500
REG1117FA-2.5	2.5/1A	DDPAK-3	KTT	−40°C to +125°C	REG1117FA2.5	REG1117FA-2.5KTTT	Tape and Reel, 50
						REG1117FA-2.5/500	Tape and Reel, 500
REG1117FA-5	5/1A	DDPAK-3	KTT	−40°C to +125°C	BB1117FA5.0	REG1117FA-5/KTTT	Tape and Reel, 50
						REG1117FA-5/500	Tape and Reel, 500
REG1117A	Adj./1A	SOT223-3	DCY	−40°C to +125°C	BB1117A	REG1117A	Rails, 80
						REG1117A	Tape and Reel, 2500
REG1117FA	Adj./1A	DDPAK-3	KTT	−40°C to +125°C	REG1117FA	REG1117FA/KTTT	Tape and Reel, 50
						REG1117FA/500	Tape and Reel, 500

(1) For the most current package and ordering information, see the Package Option Addendum located at the end of this data sheet.

ELECTRICAL CHARACTERISTICS

At T_J = +25°C, unless otherwise noted.

PARAMETER	CONDITION	REG1117, REG1117A			UNIT
		MIN	TYP	MAX	
OUTPUT VOLTAGE					
REG1117-2.85	I_O = 10mA, V_{IN} = 4.85V	2.820	2.85	2.880	V
See Note 1	I_O = 0 to 800mA, V_{IN} = 4.05V to 10V	2.790	2.85	2.910	V
REG1117-3.3	I_O = 10mA, V_{IN} = 5.3V	3.270	3.30	3.330	V
See Note 1	I_O = 0 to 800mA, V_{IN} = 4.8V to 10V	3.240	3.30	3.360	V
REG1117-5	I_O = 10mA, V_{IN} = 7V	4.950	5.00	5.050	V
See Note 1	I_O = 0 to 800mA, V_{IN} = 6.5V to 10V	4.900	5.00	5.100	V
REG1117A-1.8	I_O = 10mA, V_{IN} = 3.8V	1.782	1.8	1.818	V
See Note 1	I_O = 0 to 1A, V_{IN} = 3.8V to 10V	1.764	1.8	1.836	V
REG1117A-2.5	I_O = 10mA, V_{IN} = 4.5V	2.475	2.5	2.525	V
See Note 1	I_O = 0 to 1A, V_{IN} = 4.5V to 10V	2.450	2.5	2.550	V
REG1117A-5	I_O = 10mA, V_{IN} = 7V	4.950	5.0	5.050	V
See Note 1	I_O = 0 to 1A, V_{IN} = 7V to 10V	4.900	5.0	5.100	V
REFERENCE VOLTAGE					
REG1117 (Adjustable)	I_O = 10mA, $V_{IN} - V_O$ = 2V	1.238	1.250	1.262	V
See Note 1	I_O = 10 to 800mA, $V_{IN} - V_O$ = 1.4 to 10V	1.225	1.250	1.280	V
REG1117A (Adjustable)	I_O = 10mA, $V_{IN} - V_O$ = 2V	1.238	1.250	1.262	V
See Note 1	I_O = 10mA to 1A, $V_{IN} - V_O$ = 1.4 to 10V	1.225	1.250	1.280	V
LINE REGULATION					
REG1117-2.85(1)	I_O = 0, V_{IN} = 4.25 to 10V		1	7	mV
REG1117-3.3(1)	I_O = 0, V_{IN} = 4.8 to 10V		2	7	mV
REG1117-5(1)	I_O = 0, V_{IN} = 6.5 to 15V		3	10	mV
REG1117 (Adjustable)(1)	I_O = 10mA, $V_{IN} - V_O$ = 1.5 to 13.75V		0.1	0.4	%
REG1117A (Adjustable)(1)	I_O = 10mA, $V_{IN} - V_O$ = 1.5 to 13.75V		0.1	0.4	%
REG1117A-1.8(1)	I_O = 0, V_{IN} = 3.8V to 10V		1	7	mV
REG1117A-2.5(1)	I_O = 0, V_{IN} = 4.5V to 10V		1	7	mV
REG1117A-5.0(1)	I_O = 0, V_{IN} = 7V to 15V		3	10	mV
LOAD REGULATION					
REG1117-2.85(1)	I_O = 0 to 800mA, V_{IN} = 4.25V		2	10	mV
REG1117-3.3(1)	I_O = 0 to 800mA, V_{IN} = 4.8V		3	12	mV
REG1117-5(1)	I_O = 0 to 800mA, V_{IN} = 6.5V		3	15	mV
REG1117 (Adjustable)(1)(2)	I_O = 10 to 800mA, $V_{IN} - V_O$ = 3V		0.1	0.4	%
REG1117A (Adjustable)(1)(2)	I_O = 10mA to 1A, $V_{IN} - V_O$ = 3V		0.1	0.4	%
REG1117A-1.8(1)	I_O = 0 to 1A, V_{IN} = 3.8V		2	10	mV
REG1117A-2.5	I_O = 0 to 1A, V_{IN} = 4.5V		2	10	mV
REG1117A-5	I_O = 0 to 1A, V_{IN} = 7.0V		3	15	mV
DROPOUT VOLTAGE(3)					
All Models(1)	I_O = 100mA		1.00	1.10	V
See Note 1	I_O = 500mA		1.05	1.15	V
REG1117 Models(1)	I_O = 800mA		1.10	1.20	V
REG1117A	I_O = 1A		1.2	1.30	V
See Note 1	I_O = 1A		1.2	1.55	V

(1) Specification applies over the full specified junction temperature range, 0°C to +125°C.
(2) REG1117 and REG1117A adjustable versions require a minimum load current for ±3% regulation.
(3) Dropout voltage is the input voltage minus output voltage that produces a 1% decrease in output voltage.
(4) Percentage change in unloaded output voltage before versus after a 30ms power pulse of I_O = 800mA (REG1117 models), I_O = 1A (REG1117A), $V_{IN} - V_O$ = 1.4V (reading taken 10ms after pulse).

ELECTRICAL CHARACTERISTICS (continued)

At T_J = +25°C, unless otherwise noted.

PARAMETER	CONDITION	REG1117, REG1117A			UNIT
		MIN	TYP	MAX	
CURRENT LIMIT					
REG1117 Models	$V_{IN} - V_O$ = 5V	800	950	1200	mA
REG1117A	$V_{IN} - V_O$ = 5V	1000	1250	1600	mA
MINIMUM LOAD CURRENT					
Adjustable Models(1)(2)	$V_{IN} - V_O$ = 13.75V		1.7	5	mA
QUIESCENT CURRENT					
Fixed-Voltage Models(1)	$V_{IN} - V_O$ = 5V		4	10	mA
ADJUSTABLE PIN CURRENT(1)(2)	I_O = 10mA, $V_{IN} - V_O$ = 1.4 to 10V		50	120	µA
vs Load Current, REG1117(1)	I_O = 10mA to 800mA, $V_{IN} - V_O$ = 1.4 to 10V		0.5	5	µA
vs Load Current, REG1117A(1)	I_O = 10mA to 1A, $V_{IN} - V_O$ = 1.4 to 10V		0.5	5	µA
THERMAL REGULATION					
All Models(4)	30ms Pulse		0.01	0.1	%/W
RIPPLE REJECTION					
All Models	f = 120Hz, $V_{IN} - V_{OUT}$ = 3V + 1V_{PP} Ripple		62		dB
TEMPERATURE DRIFT					
Fixed-Voltage Models	T_J = 0°C to +125°C		0.5		%
Adjustable Models	T_J = 0°C to +125°C		2		%
LONG-TERM STABILITY					
All Models	T_A = 125°C, 1000Hr		0.3		%
OUTPUT NOISE					
rms Noise, All Models	f = 10Hz to 10kHz		0.003		%
THERMAL RESISTANCE					
Thermal Resistance, θ_{JC}	(Junction-to-Case at Tab)				
3-Lead SOT-223 Surface-Mount			15		°C/W
3-Lead DDPAK Surface-Mount	f > 50Hz		2		°C/W
	dc		3		°C/W
Thermal Resistance, θ_{JA}	(Junction-to-Case at Tab)				
3-Lead DDPAK Surface-Mount	No Heatsink		65		°C/W

(1) Specification applies over the full specified junction temperature range, 0°C to +125°C.
(2) REG1117 and REG1117A adjustable versions require a minimum load current for ±3% regulation.
(3) Dropout voltage is the input voltage minus output voltage that produces a 1% decrease in output voltage.
(4) Percentage change in unloaded output voltage before versus after a 30ms power pulse of I_O = 800mA (REG1117 models), I_O = 1A (REG1117A), $V_{IN} - V_O$ = 1.4V (reading taken 10ms after pulse).

SIMPLIFIED SCHEMATIC



TYPICAL CHARACTERISTICS

At T_A = +25°C, all models, unless otherwise noted.

SHORT−CIRCUIT CURRENT vs TEMPERATURE



LOAD REGULATION
(ΔI_{LOAD} = 800mA)



LINE REGULATION vs TEMPERATURE



RIPPLE REJECTION vs FREQUENCY



OUTPUT VOLTAGE vs TEMPERATURE



QUIESCENT CURRENT vs TEMPERATURE



TYPICAL CHARACTERISTICS (continued)

At T_A = +25°C, all models, unless otherwise noted.





APPLICATIONS INFORMATION

Figure 1 shows the basic hookup diagram for fixed-voltage models. All models require an output capacitor for proper operation, and for improving high-frequency load regulation; a 10µF tantalum capacitor is recommended. Aluminum electrolytic types of 50µF or greater can also be used. A high-quality capacitor should be used to assure that the ESR (Effective Series Resistance) is less than 0.5Ω.



Figure 1. Fixed-Voltage Model—Basic Connections

Figure 2 shows a hookup diagram for the adjustable voltage model. Resistor values are shown for some commonly-used output voltages. Values for other voltages can be calculated from the equation shown in Figure 2. For best load regulation, connect R_1 close to the output pin and R_2 close to the ground side of the load as shown.

THERMAL CONSIDERATIONS

The REG1117 has current limit and thermal shutdown circuits that protect it from overload. The thermal shutdown activates at approximately T_J = 165°C. For continuous operation, however, the junction temperature should not be allowed to exceed 125°C. Any tendency to activate the thermal shutdown in normal use is an indication of an inadequate heat sink or excessive power dissipation. The power dissipation is equal to:

$$P_D = (V_{IN} – V_{OUT})\ I_{OUT}$$

The junction temperature can be calculated by:

$$T_J = T_A + P_D\ (\theta_{JA})$$

where T_A is the ambient temperature, and θ_{JA} is the junction-to-ambient thermal resistance.



V_{OUT} (V)	R_1 (Ω)(2)	R_2 (Ω)(2)
1.25	Open	Short
1.5	750	147
2.1	158	107
2.85	169	215
3	137	191
3.3	115	187
5	113	340
10	113	787

NOTES: (1) C_3 optional. Improves high-frequency line rejection. (2) Resistors are standard 1% values.

Figure 2. Adjustable-Voltage Model—Basic Connections

A simple experiment will determine whether the maximum recommended junction temperature is exceeded in an actual circuit board and mounting configuration: Increase the ambient temperature above that expected in normal operation until the device's thermal shutdown is activated. If this occurs at more than 40°C above the maximum expected ambient temperature, then T_J will be less than 125°C during normal operation.

The internal protection circuitry of the REG1117 was designed to protect against overload conditions. It was not intended to replace proper heat sinking. Continuously running the REG1117 into thermal shutdown will degrade reliability.

LAYOUT CONSIDERATIONS

The DDPAK (REG1117F-3.3 and REG1117FA) is a surface-mount power package that has excellent thermal characteristics. For best thermal performance, the mounting tab should be soldered directly to a circuit board copper area, as shown in Figure 3. Increasing the copper area improves heat dissipation. Figure 4 shows typical thermal resistance from junction-to-ambient as a function of the copper area.



NOTE: (1) For improved thermal performance increase footprint area. See Figure 4 (*Thermal Resistance vs Circuit Board Copper Area*).

Figure 3. DDPAK Footprint



Figure 4. DDPAK Thermal Resistance versus Circuit Board Copper Area

The SOT-223 package derives heat sinking from conduction through its copper leads, especially the large mounting tab. These must be soldered to a circuit board with a substantial amount of copper remaining, as shown in Figure 5. Circuit board traces connecting the tab and the leads should be made as large as practical. The mounting tab of both packages is electrically connected to V_{OUT}.



Figure 5. SOT-223 Circuit Board Layout Example

Other nearby circuit traces, including those on the back side of the circuit board, help conduct heat away from the device, even though they may not be electrically connected. Make all nearby copper traces as wide as possible and leave only narrow gaps between traces.

Table 1 shows approximate values of θ_{JA} for various circuit board and copper areas for the SOT-223 package. Nearby heat dissipating components, circuit board mounting conditions, and ventilation can dramatically affect the actual θ_{JA}. Proper heat sinking significantly increases the maximum power dissipation at a given ambient temperature, as shown in Figure 6.

Table 1. SOT-223 θ_{JA} for Various Board Configurations

TOTAL PC BOARD AREA	TOPSIDE(1) COPPER AREA	BACKSIDE COPPER AREA	SOT-223 THERMAL RESISTANCE JUNCTION-TO-AMBIENT
2500mm^2	2500mm^2	2500mm^2	46°C/W
2500mm^2	1250mm^2	2500mm^2	47°C/W
2500mm^2	950mm^2	2500mm^2	49°C/W
2500mm^2	2500mm^2	0	51°C/W
2500mm^2	1800mm^2	0	53°C/W
1600mm^2	600mm^2	1600mm^2	55°C/W
2500mm^2	1250mm^2	0	58°C/W
2500mm^2	915mm^2	0	59°C/W
1600mm^2	600mm^2	0	67°C/W
900mm^2	340mm^2	900mm^2	72°C/W
900mm^2	340mm^2	0	85°C/W

(1) Tab is attached to the topside copper.

SOLDERING METHODS

Both REG1117 packages are suitable for infrared reflow and vapor-phase reflow soldering techniques. The high rate of temperature change that occurs with wave soldering or hand soldering can damage the REG1117.

INSPEC Abstract Number: B91007604, C91012627. Kelly, E.G. “Thermal Characteristics of Surface 5WK9Ω Packages.” The Proceedings of SMTCON. Surface Mount Technology Conference and Exposition: Competitive Surface Mount Technology, April 3−6, 1990, Atlantic City, NJ, USA. Abstract Publisher: IC Manage, 1990, Chicago, IL, USA.



Figure 6. Maximum Power Dissipation versus Ambient Temperature



Figure 7. SCSI Active Termination Configuration



Figure 8. Adjusting Output of Fixed Voltage Models



Figure 9. Regulator with Reference



Figure 10. Battery Backed-Up Regulated Supply



Figure 11. Low Dropout Negative Supply

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish	MSL Peak Temp (3)
REG1117	ACTIVE	SOT-223	DCY	4	80	TBD	CU SNPB	Level-3-220C-168 HR
REG1117-2.85	ACTIVE	SOT-223	DCY	4	80	TBD	CU SNPB	Level-3-220C-168 HR
REG1117-2.85/2K5	ACTIVE	SOT-223	DCY	4	2500	TBD	CU SNPB	Level-3-220C-168 HR
REG1117-3.3	ACTIVE	SOT-223	DCY	4	80	TBD	CU SNPB	Level-3-220C-168 HR
REG1117-3.3/2K5	ACTIVE	SOT-223	DCY	4	2500	TBD	CU SNPB	Level-3-220C-168 HR
REG1117-5	ACTIVE	SOT-223	DCY	4	80	TBD	CU SNPB	Level-3-220C-168 HR
REG1117-5/2K5	ACTIVE	SOT-223	DCY	4	2500	TBD	CU SNPB	Level-3-220C-168 HR
REG1117/2K5	ACTIVE	SOT-223	DCY	4	2500	TBD	CU SNPB	Level-3-220C-168 HR
REG1117A	ACTIVE	SOT-223	DCY	4	80	TBD	CU SNPB	Level-3-220C-168 HR
REG1117A-1.8	ACTIVE	SOT-223	DCY	4	80	TBD	CU SNPB	Level-3-220C-168 HR
REG1117A-1.8/2K5	ACTIVE	SOT-223	DCY	4	2500	TBD	CU SNPB	Level-3-220C-168 HR
REG1117A-2.5	ACTIVE	SOT-223	DCY	4	80	TBD	CU SNPB	Level-3-220C-168 HR
REG1117A-2.5/2K5	ACTIVE	SOT-223	DCY	4	2500	TBD	CU SNPB	Level-3-220C-168 HR
REG1117A/2K5	ACTIVE	SOT-223	DCY	4	2500	TBD	CU SNPB	Level-3-220C-168 HR
REG1117F-3.3	OBSOLETE	DDPAK/ TO-263	KTT	3		TBD	Call TI	Call TI
REG1117F-3.3/500	ACTIVE	DDPAK/ TO-263	KTT	3	500	Green (RoHS & no Sb/Br)	CU SN	Level-2-260C-1 YEAR
REG1117F-3.3KTTT	ACTIVE	DDPAK/ TO-263	KTT	3	50	Green (RoHS & no Sb/Br)	CU SN	Level-2-260C-1 YEAR
REG1117FA	OBSOLETE	DDPAK/ TO-263	KTT	3		TBD	Call TI	Call TI
REG1117FA-1.8	OBSOLETE	DDPAK/ TO-263	KTT	3		TBD	Call TI	Call TI
REG1117FA-1.8/500	ACTIVE	DDPAK/ TO-263	KTT	3	500	Green (RoHS & no Sb/Br)	CU SN	Level-2-260C-1 YEAR
REG1117FA-1.8KTTT	ACTIVE	DDPAK/ TO-263	KTT	3	50	Green (RoHS & no Sb/Br)	CU SN	Level-2-260C-1 YEAR
REG1117FA-2.5	OBSOLETE	DDPAK/ TO-263	KTT	3		TBD	Call TI	Call TI
REG1117FA-2.5/500	ACTIVE	DDPAK/ TO-263	KTT	3	500	Green (RoHS & no Sb/Br)	CU SN	Level-2-260C-1 YEAR
REG1117FA-2.5KTTT	ACTIVE	DDPAK/ TO-263	KTT	3	50	Green (RoHS & no Sb/Br)	CU SN	Level-2-260C-1 YEAR
REG1117FA-5.0	OBSOLETE	DDPAK/ TO-263	KTT	3		TBD	Call TI	Call TI
REG1117FA-5.0/500	ACTIVE	DDPAK/ TO-263	KTT	3	500	TBD	CU SN	Level-3-235C-168 HR
REG1117FA-5.0KTTT	ACTIVE	DDPAK/ TO-263	KTT	3	50	TBD	CU SN	Level-3-235C-168 HR
REG1117FA/500	ACTIVE	DDPAK/ TO-263	KTT	3	500	Green (RoHS & no Sb/Br)	CU SN	Level-2-260C-1 YEAR
REG1117FA2.5KTTTG3	ACTIVE	DDPAK/ TO-263	KTT	3	50	Green (RoHS & no Sb/Br)	CU SN	Level-2-260C-1 YEAR
REG1117FAKTTT	ACTIVE	DDPAK/ TO-263	KTT	3	50	Green (RoHS & no Sb/Br)	CU SN	Level-2-260C-1 YEAR

(1) The marketing status values are defined as follows:
ACTIVE: Product device recommended for new designs.
LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.
NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.
PREVIEW: Device has been announced but is not in production. Samples may or may not be available.
OBSOLETE: TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS) or Green (RoHS & no Sb/Br) - please check http://www.ti.com/productcontent for the latest availability information and additional product content details.
TBD: The Pb-Free/Green conversion plan has not been defined.
Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.
Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

MPDS094A – APRIL 2001 – REVISED JUNE 2002

DCY (R-PDSO-G4) **PLASTIC SMALL-OUTLINE**



NOTES: A. All linear dimensions are in millimeters (inches).
B. This drawing is subject to change without notice.
C. Body dimensions do not include mold flash or protrusion.
D. Falls within JEDEC TO-261 Variation AA.

KTT (R–PSFM–G3) PLASTIC FLANGE–MOUNT PACKAGE



NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Body dimensions do not include mold flash or protrusion. Mold flash or protrusion not to exceed 0.005 (0,13) per side.
D. Falls within JEDEC TO–263 variation AA, except minimum lead thickness and minimum exposed pad length.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		**Applications**	
Amplifiers	amplifier.ti.com	Audio	www.ti.com/audio
Data Converters	dataconverter.ti.com	Automotive	www.ti.com/automotive
DSP	dsp.ti.com	Broadband	www.ti.com/broadband
Interface	interface.ti.com	Digital Control	www.ti.com/digitalcontrol
Logic	logic.ti.com	Military	www.ti.com/military
Power Mgmt	power.ti.com	Optical Networking	www.ti.com/opticalnetwork
Microcontrollers	microcontroller.ti.com	Security	www.ti.com/security
		Telephony	www.ti.com/telephony
		Video & Imaging	www.ti.com/video
		Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments
Post Office Box 655303 Dallas, Texas 75265

Copyright © 2005, Texas Instruments Incorporated